



MATERIAL SAFETY DATA SHEET

Wynn's Professional Products All-Weather Viscotene - Aerosol

WYNN'S
A division of Illinois Tool Works Inc.
1151 West Fifth Street
Azusa, California 91702

EMERGENCY TELEPHONE NUMBER:
Chemtrec (800) 424-9300
INFORMATION TELEPHONE NUMBER:
Wynn's (626) 334-0231

PRODUCT IDENTIFICATION

PRODUCT NAME	EFFECTIVE DATE	PRODUCT CODE
Wynn's Professional Products All-Weather Viscotene - Aerosol	12-16-05	80608, 80609

CHEMICAL NAME	CAS NUMBER
N/A	N/A

HAZARDOUS INGREDIENTS

COMMON NAME	CHEMICAL NAME	CAS NO.	OSHA PEL	ACGIH TLV-TWA
Heptane	n-Heptane	142-82-5	500	400 ppm
Methyl Acetate	Methyl ester acetic acid	79-20-9	200 ppm	200 ppm
Petroleum Hydrocarbon	Petroleum Oil	64742-58-1	5 mg/m ³	5 mg/m ³
Carbon Dioxide	Carbonic Anhydride	124-38-9	5000 ppm	5000 ppm

Contains no other ingredients now known to be hazardous as defined by OSHA 29CFR 1910.1000(z) and 29CFR 1910.1200.

PHYSICAL DATA

These data are approximate or typical values and should not be used as precise specifications. Unless otherwise noted values are at 20°C(68°F) and 760 mmHg (1 atm).

Boiling Point/Range	136 to 600 °F (58 to 316°C)	Freeze Point	N/D °F(°C)
Specific Gravity (H₂O=1) @ 15.6°C	0.78	Vapor Pressure (PSIG)	70
Vapor Density (Air =1)	>1	Solubility in Water (%)	Slight
% Volatiles by Volume (CARB)	46%	Evaporation Rate (Butyl Acetate = 1)	>1
pH (as is)	N/A	pH (dilute) @ %	N/A
Appearance	Clear, light amber liquid	Odor	Hydrocarbon

N/D - Not Determined

N/A - Not Applicable

< = Less Than

> = Greater Than

FIRE AND EXPLOSION HAZARD DATA

Flash Point 14°F(-10 °C) **Method** Tag Closed Cup

Flammable or Explosive Limits (Approximate percent by volume in air)

Lower (LEL) N/D

Upper (UEL) N/D

Hazard Class Identification

	Flammability 4		Hazard Code 0 - Least (insignificant)
Health 2		Reactivity 0	1 - Slight
	Other --		2 - Moderate
			3 - High
			4 - Extreme

Extinguishing Media

Carbon dioxide, dry chemicals, foam.

Special Fire Fighting Procedures

Use water to cool fire exposed containers. Fire fighters wear a suit contained breathing apparatus.

Unusual Fire and Explosion Hazards

Aerosol cans may rupture when exposed to heat.

REACTIVITY DATA

Stability

Stable.

Conditions to Avoid

Avoid spraying around open flame. Avoid high temperature sources.

Materials to Avoid

Strong oxidizers

Hazardous Decomposition or Combustion Products

Thermal decomposition will produce carbon monoxide, carbon dioxide, sulfur and nitrogen oxides.

Hazardous Polymerization (conditions)

Will not occur.

HEALTH HAZARDS/ROUTES OF ENTRY

Signs, Symptoms and Effects of Overexposure

Ingestion (swallowing) Harmful if swallowed. Can cause vomiting, dizziness, headaches, loss of coordination. Aspiration hazard.

Skin Contact Irritant to skin. Can cause defatting of skin, redness, dryness, cracking of skin.

Eye Contact Can cause irritation. Direct contact with the liquid causes stinging, tearing, blurred vision, pain.

Inhalation (breathing) Anesthetic effect. May cause irritation to the upper respiratory tract. May cause dizziness, nausea, vomiting.

Other Effects of Prolonged/Repeated Overexposure

This material has not been identified as a carcinogen by NTP, IARC or OSHA. Can cause skin and eye irritation. In confined area, vapors in high concentrations are anesthetic. Irritant to upper respiratory system. Over exposure to solvents may cause nervous system, kidney and liver damage.

EMERGENCY AND FIRST AID PROCEDURES

Ingestion (swallowing) Call a physician immediately. DO NOT induce vomiting.

Skin Contact Wash with soap and water. Remove contaminated clothes.

Eye Contact Flush with water for 15 minutes. If irritation persists, call a physician immediately.

Inhalation (breathing) Remove person to fresh air to avoid further inhalation.

SPILL OR RELEASE CONTROL PROCEDURES

Steps to be taken in case material is released or spilled

Eliminate all ignition sources. Ventilate area & restrict entry. Wear protective equipment. Absorb with inert absorbent. KEEP LIQUID OUT OF SEWERS AND WATER WAYS.

Waste Disposal Method

DO NOT incinerate. Dispose of in accordance with Federal, State and Local regulations. Under RCRA regulations it is an ignitable waste.

EPA Reportable Quantity (RQ), 40CFR302 (CERCLA104)

N/A

EPA Toxic Chemical Release Reporting, 40CFR372(SARA313)

Chemical	CAS NO.	% in Product
N/A	N/A	N/A

HANDLING AND STORAGE

Handling and Storage Precautions

DANGER: Harmful if inhaled. Avoid breathing of vapors, spray mist. Use in well ventilated area. Avoid skin and eye contact. KEEP AWAY from heat, sparks, open flame.

Other Precautions

DO NOT PUNCTURE
DO NOT INCINERATE.
KEEP OUT OF REACH OF CHILDREN.

PERSONAL PROTECTION - EXPOSURE CONTROL

Ventilation

Provide explosion proof local exhaust to keep exposure concentrations below TLV & LEL limits.

Respiratory Protection

If personal exposure cannot be controlled below TLV limits, wear properly fitted respirator approved by NIOSH/MSHA for protection against hazardous ingredients.

Eye Protection

Safety goggles.

Protective Gloves

Impervious gloves.

Other Protective Clothing or Equipment

None special.

Work/Hygienic Practices

Personal cleanliness is always appropriate. Frequent washing minimizes chances of inadvertent exposure.

TRANSPORTATION INFORMATION

Department of Transportation (DOT) Classification

	Flammable Liquid		Corrosive
	Flammable Solid		Non-Flammable Gas
XXX	Flammable Gas		Not Hazardous by DOT
	Combustible Liquid		Other:

DOT Proper Shipping Name

Aerosols, flammable.
(Consumer Commodity, ORM-D may be used for ground transportation within the U.S.A.)

DOT ID Number

UN 1950

DOCUMENTATION

Product Code No.: 80608, 80609
Previous Code No.:80608, 80609

Issue Date: 12-16-05
Prior Date: 04-30-03

This information is, to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use.