

**MSDS - Material Safety Data Sheet****Product Name: LIQUID WRENCH WHITE LITHIUM GREASE WITH CERFLON**

MSDS No.: L616

**I. Basic Information:****Manufacturer:** RADIATOR SPECIALTY COMPANY**Contact:** Robert Geer**Address:** 600 RADIATOR ROAD**Information Telephone Number:** 704-684--181 1**City, ST Zip:** INDIAN TRAIL, NC 28079**Emergency Contact:** RMPDC (877-740-5015)**Country:****Emergency Telephone Number:** 303-623-5716**Emergency Restrictions:****Product Name:** LIQUID WRENCH WHITE LITHIUM GREASE WITH CERFLON**MSDS No.:** L616**Issue Date:** 03/10/2011**Supersedes Date:** 06/03/2008**II. Hazards Identification:****EMERGENCY OVERVIEW**

Danger: Flammable. Harmful or fatal if swallowed. Eye and skin irritant. Contents under pressure.

Level 3 Aerosol

**OSHA Regulatory Status**

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**Potential Health Effects****Route(s) of Entry:**

Absorption, Inhalation, and Ingestion.

**Health Hazards (Acute and Chronic):**

See signs and symptoms below

**Signs and Symptoms:**

Eye Contact: Irritant. Prolonged contact may cause conjunctivitis.

Skin Contact: Irritant. Defatting of tissue, dermatitis may occur.

Inhalation: Irritant to mucous membranes. Repeated exposure may cause narcosis..

Ingestion: HARMFUL OR FATAL IF SWALLOWED. May cause burns to mouth, throat &amp; stomach.

**Medical Conditions Generally Aggravated by Exposure:**

None known

**Other Health Warnings:**

Aspiration of vomitus into the lungs can cause pneumonitis, which can be fatal.

**Potential Environmental Effects**

Not Available

**III. Composition/Information on Ingredients:**

Chemical Name	CAS No.	% Range	Trade Secret
1,2,4-Trimethylbenzene	95-63-6	1.0 - 5.0	
Aliphatic Hydrocarbon Solvent	8052-41-3	60.0 - 100.0	
Carbon dioxide	124-38-9	1.0 - 5.0	
Lithium Grease	Proprietary	10.0 - 30.0	
Mesitylene	108-67-8	1.0 - 5.0	
Naphthenic Petroleum Distillate	64742-52-5	10.0 - 30.0	
Xylene (mixed isomers)	1330-20-7	1.0 - 5.0	

## ***MSDS - Material Safety Data Sheet***

### ***Product Name: LIQUID WRENCH WHITE LITHIUM GREASE WITH CERFLON***

***MSDS No.: L616***

#### ***IV. First Aid Measures:***

##### **Emergency and First Aid Procedures:**

Eye Contact: Flush eyes with clean water for 15 minutes while lifting eyelids. Get prompt medical attention.

Skin Contact: Wash with soap and water thoroughly. If adverse effects persist, get prompt medical attention. Launder contaminated clothing before reuse.

Inhalation: Remove to fresh air. If breathing becomes difficult get prompt medical attention.

Ingestion: DO NOT INDUCE VOMITING! Call Poison Control Center, physician, or hospital emergency room immediately.

##### **Note to Physicians:**

N/E

#### ***V. Fire Fighting Measures:***

##### **Suitable Extinguishing Media:**

Water Fog, Foam, Carbon Dioxide, Dry Chemical

##### **Unsuitable Extinguishing Media:**

Do not use forced water stream as this could cause the fire to spread. Use shield to protect from rupturing and venting containers.

##### **Products of Combustion:**

Normal products of combustion, smoke, carbon dioxide, carbon monoxide, and sulfur trioxides.

##### **Protection of Firefighters:**

Wear self-contained positive pressure breathing apparatus and protective clothes. Use shield to protect from rupturing and venting containers. At elevated temperatures containers may vent, rupture or burst, even violently

#### ***VI. Accidental Release Measures:***

##### **Personal Precautions:**

Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

##### **Environmental Precautions:**

Prevent run-off to sewers, streams, or other bodies of water. If run-off occurs, notify proper authorities as required that a spill has occurred. Run off to sewer may create fire or explosion hazard.

##### **Methods for Containment:**

Dike or contain spill and absorb with inert materials (sand, sawdust, absorbent sweeping compounds, rags, etc).

##### **Methods for Cleanup:**

Using a non-metallic scoop, place contaminated material into an approved chemical waste container. Where possible, vacuum spilled liquid using an explosion proof vacuum to recover material.

##### **Other Information:**

If run-off occurs, notify proper authorities as required that a spill has occurred.

#### ***VII. Handling and Storage:***

##### **Handling Precautions:**

Use with adequate ventilation and proper protective equipment.

Do not use or store near fire, sparks, or open flame. Do not puncture or incinerate container.

##### **Storage Precautions:**

Store in cool, well ventilated area below 120°F away from heat, fire, sparks or flame. Exposure to temperatures above 120° may cause container to vent, rupture, or burst. Do not store with strong oxidizing agents

#### ***VIII. Exposure Controls/Personal Protection:***

## *MSDS - Material Safety Data Sheet*

### *Product Name: LIQUID WRENCH WHITE LITHIUM GREASE WITH CERFLON*

*MSDS No.: L616*

<b>Chemical Name</b>	<b>OSHA PEL</b>	<b>ACGIH TLV</b>	<b>Other Limits</b>
Lithium Grease	N/E	N/E	Not Available
Carbon dioxide	N/AV	5000 ppm	Not Available
Aliphatic Hydrocarbon Solvent	100 ppm	100 ppm	Not Available
1,2,4-Trimethylbenzene	N/E	25 ppm	Not Available
Mesitylene	N/A	N/A	Not Available
Xylene (mixed isomers)	100 ppm	100 ppm	Not Available
Naphthenic Petroleum Distillate	5 mg/m3	5 mg/m3	Not Available

#### **Engineering Controls:**

See above for applicable exposure limits. Maintain adequate ventilation.

Avoid breathing vapors. In restricted areas, use approved chemical filters designed to remove vapor. In confined areas, use approved air line type respirator or hood. A self-contained breathing apparatus is required for vapor concentrations above TLV limits.

#### **Personal Protective Equipment:**

For prolonged exposure wear protective safety glasses, gloves, and apron.

### ***IX. Physical and Chemical Properties:***

**Boiling Point:** 320°F

**Boiling Range:** N/D

**Solubility In Water:** Insoluble

**Flash Point:** 84°F

**Odor Threshold:** N/D

**Vapor Density (AIR = 1):** N/D

**pH Range:** N/A

**Decomposition Temp:** N/D

**Lower Explosive Limit:** 0.7%

**Specific Gravity (H2O = 1):** 0.80

**Other Information:** VOC Content: 78%

**Melting Point:** N/A

**Freezing Point:** N/D

**Evaporation Rate (Butyl Acetate = 1):** N/D

**Flash Point Method:** TCC

**Appearance and Odor:** Opaque dense off white suspension with petroleum odor

**Vapor Pressure (mm Hg.):** N/D

**Partition Coefficient:** N/D

**Auto-Ignition Temp:** N/D

**Upper Explosive Limit:** 7.0%

### ***X. Stability and Reactivity:***

#### **Stability:**

Stable

#### **Conditions to Avoid:**

N/D

#### **Incompatible Materials:**

Avoid strong oxidizers.

#### **Hazardous Decomposition Products:**

Normal products of combustion, smoke, carbon dioxide, carbon monoxide, and sulfur trioxides.

#### **Possibility of Hazardous Reactions:**

Will not occur

**MSDS - Material Safety Data Sheet****Product Name: LIQUID WRENCH WHITE LITHIUM GREASE WITH CERFLON**

MSDS No.: L616

**XI. Toxicological Information:**

N/D

**XII. Ecological Information:**

N/D

**XIII. Disposal Considerations:**

DISPOSAL: This container may be recycled in aerosol recycling centers when empty. Before offering for recycling, empty the can by using the product according to the label. DO NOT PUNCTURE! If recycling is not available, wrap the container and discard in the trash. Dispose of unused product in accordance with all local, state government and federal laws and regulations.

**XIV. Transport Information:****Shipping Name:** Consumer Commodity**DOT Hazard Class:** ORM-D**DOT Subsidiary Hazard Class:** Not Available**UN/NA#:** Not Available**Packing Group:** Not Available**Transportation Information:**

DOT Hazard Class: ORM-D

Shipping Name: Consumer Commodity

The DOT description is provided to assist in the proper shipping classification of this product and may not be suitable for international and air shipping purposes.

ICAO/IATA (US)

Shipping Name: Aerosols

Class: 2.1

UN number: UN1950

International:

ICAO/IATA

UN number: UN1950

Shipping Name: Aerosols

Class: 2.1

IMDG

UN number: UN1950

Shipping Name: Aerosols

Class: 2.1

EmS: F-D, S-U

**XV. Regulatory Information:**

SARA 313 Chemicals:

Xylene 1330-20-7

1,2,4-Trimethylbenzene 95-63-6

USA TSCA: All components of this material are listed on the US TSCA Inventory.

PROPOSITION 65 WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects and other reproductive harm.

State RTK Chemicals:

Aliphatic Hydrocarbon 8052-41-3

1,2,4-Trimethylbenzene 95-63-6

1,3,5-Trimethylbenzene 108-67-8

Xylene 1330-20-7

## MSDS - Material Safety Data Sheet

**Product Name: LIQUID WRENCH WHITE LITHIUM GREASE WITH CERFLON**

MSDS No.: L616

### **XVI. Other Information:**

**Chemical State:**     Liquid     Gas     Solid

**Chemical Type:**     Pure     Mixture

**Hazard Category:**


Acute     Chronic     Fire  
 Pressure     Reactive



#### **Additional Manufacturer Warnings:**

Do not used in confined area without proper ventilation. Contact lenses may cause further damage in case of splash into eye. KEEP AWAY FROM CHILDREN AND ANIMALS!

N/E: Not Established  
N/D: Not Determined  
N/A: Not Applicable  
N/AV: Not Available



#### **Additional Product Information:**

While Radiator Specialty Company believes this data is accurate as of the revision date, we make no warranty with respect to the data and we expressly disclaim all liability for reliance thereon. The data is offered solely for information, investigation, and verification. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this MSDS. The user is responsible for full compliance.